

DigiCam Surveillance

415 Sony 1/3" CCD Color Day/Night CCD Indoor Professional 380 TV Lines Camera

The 415 pro-series box camera is an affordable answer to your indoor security needs. The Sony super HAD image sensor paired up with the .1 LUX on this camera makes sure that you can see things clearly, even in low light situations. This camera also supports various lens configurations in C/CS mount with fixed or Vari-focal auto iris lenses. This camera also fits perfectly inside our outdoor weatherproof camera housings. The 415 has the ability to take advantage of either AC or DC power so you are sure to get just what you need. **FEATURES**

- Sony 1/3 inch Super HAD Color CCD image sensor
- Pixel number: EIA=270,000 / CCIR=320,000 (Normal Resolution)
- Reduced fixed pattern noise and lag. No sticking and no image distortion. Blooming suppression.
- Auto Electronic Shutter (AES), Auto Gain Control (AGC), Back Light Compensation (BLC)
- Supports both C and CS mount lenses.
- Supports both Video-Drive & DC-Drive auto iris lens.
- AC/DC Switchable
- **Lens sold separately**



SPECIFICATIONS

Image Sensor	1/3 inch Sony Color CCD image sensor
Resolution	380 TV lines
Minimum Illumination	0.05 Lux / F1.2
Lens Furnished	Lens sold separately
Power Source	AC 24V / 110V
Power Consumption	3.5W
Number of Pixel	EIA: 510*492, CCIR: 500*582 (H*V)
S/N Ratio	More than 48dB
Electronic Shutter	EIA: 1/60s~1/100,000s, CCIR: 1/50s~1/110,000s ON/OFF Switch-able
Auto Iris	Video-Drive Lens & DC-Drive Lens both supported
Load Impedance	75 Ohms
Lens Mount	C/CS mount changeable
Power Source	DC 12V -- AC24/110/230/240V
Current Consumption	1.32 W -- .98 W
White Balance	ATW (Auto) / MWB (Manual) switch-able.(2500K~9500K)
Lens Mount	C/CS mount changeable
Load Impedance	1 Vp-p / 75 Ohms. BNC or F connector
Operating Temp	-10 ~ 50 (14 ~ 122)
Sync. System	Negative sync. Internal / Line Lock (phase adjustable) mode switch-able.
Back Light Compensation	ON/OFF Switch-able