

DigiCam Surveillance

500' White RG59 Siamese Video/Power Cable



Specifications

- Siamese type configuration with separation web
- RG-59/U Type coax plus one pair 18 AWG stranded
- (Coax) solid bare copper conductor 20 AWG
- Gas injected polyethylene coaxial core Nom. OD .142 inch (3.61 mm) with an aluminum polyester tape barrier
- Bare copper braid shield 95% coverage
- Unshielded 18 AWG twisted pair employing PVC insulation and PVC fillers
- Overall PVC jacket Nom. OD .232 x .460" (5.89 x 11.68 mm)

Applications:

- Indoor cable (non-conduit per NEC) for CCTV

Rating as per NEC:

- UL listed NEC type CM as defined in Article 800
- C(UL)+ listed CMH
- Constructed in accordance with UL Standard 444
- Listed as being resistant to the spread of fire as defined in Section 800 of the National Electric Code.

Installation Characteristics:

- Minimum Bend Radius: 2.5"
- Maximum Pulling Tension: 45 lbs.

Color Code:

- Conductors: 1. Black, 2. Red
- Jacket Color: Black

Special Notes:

+C(UL) CMH Canadian UL accepted mark replaces PCC-FT1 Rev. 1. 1/2000

Electrical Characteristics:

- Nominal capacitance: 16.2 pf/ft 53.1 pf/m*
- Vel. of Prop.: 82%
- Nominal Impedance: 75Ω
- 20 AWG Nom. D.C.R. @ 20°C: 10.1Ω/1000 ft.