

DigiCam Surveillance
 digicamsurveillance.com



DVR410 4 Channel Economy DVR

Features

- Multi Functional, Live/Record/Play Back/Backup/Internet
- Dual Stream, M-JPEG Recording & MPEG 4 Transmitting Over Internet
- Enhanced Picture Quality
- Faster Internet Transmitting
- Audio Included When Remote Backup/USB Backup
- IE Browser Supported
- Completed Networking Supported, TCP/IP, PPPoE, DHCP, DDNS
- Frame Rate Adjustable Under Each Mode Per Each Channel
- Max 2 x HDD x 500g Supported
- OSD/PTZ Mouse Control Supported



Video I/F	NTSC/PAL Auto Detect
Video Input	4 Channel input 1.0Vp-p, 75ohm unbalanced (BNC type)
Video Output	main-monitor composite (BNC type) x 1
Horizontal Resolution	640 x 448 (NTSC) / 640 x 544 (PAL)
S/N Ratio	More than 40dB
Color	16.7 million
Screen Quality	Full: 640 x 448 active pixels (NTSC) / 640 x 544 active pixels (PAL) Quad Screen: 320 x 224 active pixels (NTSC) / 320 x 272 active pixels (PAL)
Display Rate	120 fps (NTSC) / 100 fps (PAL)
Recording Rate	Max 60 fps (NTSC) / 50 fps (PAL)
Recording Resolution	640 x 224 (NTSC) / 640 x 272 (PAL)
Adjustable Recording Speed	60 ~ 0 fps (NTSC); Max 50 ~ 0 fps (PAL)
Record Quality	High, normal, low
Compress Method	Storage: MJPEG, Network/internet: MPEG4
Recording Control	Auto / Manual / Schedule / Motion / Alarm
Playback Mode	Time List / Event List / Date & Time Search
Motion Detection	16 x 16 grids camera for all channel
Alarm Function	4 input / 1 output
Backup	USB1.1/2.0 memory and network remote backup
Storage	HDD x 2 (max 1T)
Audio Input	RAC x 1
Audio Output	RAC x 1
Web Interface	Support licensed software AP
Network Connection	TCP/IP, PPPoE, DHCP, DDNS
Power Supply	DC12V / 5A
Dimension	426 (W) x 328.5 (D) x 73 (H) mm
Operating Temp	41 deg. F ~ 104 deg. F (5 deg. C ~ 40 deg. C)
Operating Humidity	Less than 90%

